

## Model : FE303XS



\* controller panel is optional

### Product specifications

#### Input voltage

90V~240VAC single phase 1.5A(50,60HZ)

#### Accelerator supply (Referenced to GND)

Output voltage: -1kV~-30kV  
 Absolute voltage accuracy: Less than 0.1%  
 Set ability: 16bit (0.5V LSB)  
 Output current: 200  $\mu$  A max  
 Ripple noise: 3ppm 90mVp-p or less@30kV  
 Stability: 30ppm/1hr after 1hr warm up  
 temperature coefficient: 20ppm/ $^{\circ}$ C

#### Filament supply (Referenced to Accelerator)

Output voltage: 0~5V  
 Set ability: 16bit (1mA LSB)  
 Output current: 0~3.2A  
 Ripple noise: Less than 10mA @3A  
 Absolute current accuracy:  $\pm$ 0.01A  
 Stability: 100ppm/1hour @ 3.0A  
 temperature coefficient: 50ppm/ $^{\circ}$ C

#### Suppressor supply (Referenced to Accelerator)

Output voltage: -0.03kV~ -0.6kV  
 Absolute voltage accuracy: Less than 1.0% @300V  
 Set ability: 14bit (0.11V LSB)  
 Output current: 150  $\mu$  A max  
 Ripple noise: Less than 20mVp-p  
 Stability: 50ppm/1hr after 1hr warm up  
 temperature coefficient: 25ppm/ $^{\circ}$ C

#### Extractor supply (Referenced to Accelerator)

Output voltage: +0.4kV~+8.0kV  
 Absolute voltage accuracy: Less than 0.1%  
 Set ability: 16bit (0.16V LSB)  
 Output current: 200  $\mu$  A max  
 Ripple noise: Less than 100mVp-p @4.0kV  
 Stability: 50ppm/1hr after 1hr warm up  
 temperature coefficient: 25ppm/ $^{\circ}$ C

#### Electric static lens supply (Referenced to Accelerator)

Output voltage: -0.3K~-15kV  
 Absolute voltage accuracy: Less than 0.1%  
 Set ability: 16bit (0.1V LSB)  
 Output current: 180  $\mu$  A max  
 Ripple noise: Less than 100mVp-p  
 Stability: 30ppm/1hr after 1hour warm up  
 temperature coefficient: 20ppm/ $^{\circ}$ C

optional

Custom multiple output power supply for "TFE-type scanning electron microscope".

### Application

- Scanning electron microscope
- Electron probe micro analyzer
- FE-Auger electron microscopy

### The other specifications

All the outputs provide with the over voltage protection and the over current protection.

External control: Optical isolated RS232C

Interlock: vacuum, thermo, HV-connection

HV connector: Customer specification

Output monitor: Accelerating voltage, Lens voltage

Storage temp range: -5 $^{\circ}$ C~ +40 $^{\circ}$ C

Operating temperature

Limit: +10 $^{\circ}$ C~ +40 $^{\circ}$ C

Humidity: 80% or less

Insulation method: Air insulation (one molding)

Externals size: 480mm(W)  $\times$  450(D)  $\times$  249 (H)

Weight: 33kg

The model "FE303XS" is an integrated multiple output high voltage power supply specifically developed for TFE type scanning electron microscope.

\* Please ask details.  
 e-mail [info@futex.jp](mailto:info@futex.jp)

FUTEX CO., LTD. <http://www.futex.jp>  
 TEL:+81-42-549-2888 FAX:+81-42-549-2900  
 2-28-3 Fukujima-cho Akishima Tokyo, Japan

Update: Nov,30, 2011